

GENAXY HOT AIR OVEN

Double walled inside made of thick anodized Aluminum/Stainless Steel 304 quality and outside and Mild Steel furnished in Epoxy Powder Coating. The gap of 75mm between two walls is filled with pure mineral wool. Synthetic rubber gasket is provided on the door for better grip.

Heating elements are placed in ribs at the bottom and sides. Adjustable air ventilators are placed near the top of the sides. The temperature is controlled by an Electronic Digital Controller cum Indicator from room few °C above ambient to 250 °C with sensitivity of plus minus 0.5 deg. C . Supplied complete with two pilot lamps , perforated shelves adjustable at any level having arrangement to fit the automatic timer to works on 220/230 volts A.C. cord and plug. Complete with air circulating fan.

Technical Specification

Catalog No.	Inner Chamber	Size	Capacity
GEN-OSA-1	Aluminium	300 X 300 X 300mm	28
GEN-OSS-1	Stainless Steel	300 X 300 X 300mm	28
GEN-OSA-2	Aluminium	355 X 355 X 355mm	45
GEN-OSS-2	Stainless Steel	355 X 355 X 355mm	45
GEN-OSA-3	Aluminium	455 X 455 X 455mm	95
GEN-OSS-3	Stainless Steel	455 X 455 X 455mm	95
GEN-OSA-4	Aluminium	455 X 455 X 605mm	125
GEN-OSS-4	Stainless Steel	455 X 455 X 605mm	125
GEN-OSA-5	Aluminium	605 X 605 X 605mm	224
GEN-OSS-5	Stainless Steel	605 X 605 X 605mm	224
GEN-OSA-6	Aluminium	605 X 455 X 910mm	252
GEN-OSS-6	Stainless Steel	605 X 455 X 910mm	252
GEN-OSA-7	Aluminium	605 X 605 X 910mm	336
GEN-OSS-7	Stainless Steel	605 X 605 X 910mm	336

**Genaxy Scientific Pvt. Ltd .**

155-156, C-Block, Community Centre, Plot 32 to 57, Behind Janak Cinema, Janak Puri, New Delhi-110 058

Phones : +91-11-4761 9999 (100 Lines) Fax : +91-11-2553 4163

E-mail : info@genaxy.com